Eaton 5P1150IRG2 alimentation d'énergie non interruptible Interactivité de ligne 920 W 6 sortie(s) CA

Marque : Eaton

Code produit: 5P1150IRG2

Nom du produit : 5P1150IRG2



Eaton 5P1150IRG2. Topologie UPS: Interactivité de ligne, Puissance de sortie: 920 W, Forme d'onde: Sinus. Types de sortie AC: Coupleur C13, Prise mâle: Coupleur C14, Nombre de prises en sortie: 6 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Capacité de la batterie: 9 Ah, Tension des piles: 6 V. Format: Tower, Couleur du produit: Noir, Argent, Capacité du rack: 1U. Certification: IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 UL 1778 CSA-C22.2 CE UKCA Cm Ukr KCC cTUVus BIS



onduleur.shop

Caractéristiques	
Topologie UPS *	Interactivité de ligne
Puissance de sortie *	920 W
Forme d'onde *	Sinus
Tension de voltage à l'entrée (min) *	150 V
Tension de voltage à l'entrée (max) *	294 V
Fréquence d'entrée *	50/60 Hz
Tension de voltage à la sortie (max)	240 V
fréquence de sortie	50/60 Hz
Régulateur de tension automatique (AVR)	✔
Dissipation thermique	465 BTU/h
Nombre de phases d'entrée	1
Nombre de phases de sortie	1
Efficacité	98,2%
Niveau sonore	35 dB

Connectivité	
Types de sortie AC	Coupleur C13
Prise mâle	Coupleur C14
Nombre de prises en sortie	6 sortie(s) CA
Port USB	✔
Type de port USB	USB Type-B
Interface série	✔
Type d'interface série	RS-232
Nombre de ports série	1

Batterie	
Technologie batterie	Sealed Lead Acid (VRLA)
Capacité de la batterie	9 Ah
Tension des piles	6 V
Nombre de batteries prises en charge	4

Design	
Format *	Tower
Capacité du rack	1U
Couleur du produit *	Noir, Argent
Type d'écran	LCD

Conditions environnementales	
Température d'opération	0 - 40 °C
Humidité relative de fonctionnement (H-H)	0 - 90%
Altitude de fonctionnement	0 - 3000 m

Certificat	
Certification	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 UL 1778 CSA-C22.2 CE UKCA Cm Ukr KCC cTUVus BIS

Contenu de l'emballage	
Manuel d'utilisation	✔
Guide d'installation rapide	✔

Poids et dimensions	
Largeur	438 mm
Profondeur	509 mm
Hauteur	43,2 mm
Poids	14,2 kg

9321289227485

Catalog Object Cloud

onduleur.shop

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 02-NOV-2026. Prints or copies of Information are only valid on the printed Publication date